


FRAUNHOFER INSTITUTE FOR APPLIED POLYMER RESEARCH IAP







- 1, 2 Polymeric ultrasonic transducer.
- 3 Piezoelectric touch sensor.

SENSORS AND ACTUATORS

Fraunhofer IAP provides research on and

development of functional materials and

devices for different sensor and actuator

purposes. The main application fields are

material development, processing and characterization as well as embedding of electro-

active polymers (EAP) in electromechanical

transducers which work in the piezoelectric

or electrostrictive sensor or actuator modes.

As piezoelectric materials, classical ferro-

electric polymers, polymer-ceramic composites, and newly developed cellular

polymer foams (so-called ferroelectrets)

are investigated and adapted for different

applications such as structured large-area

sensors, touch pads, and ultrasonic sensors

Fraunhofer Institute for Applied Polymer Research IAP

Potsdam-Golm Science Park Geiselbergstr. 69 14476 Potsdam

Contact

Priv.-Doz. Dr. Michael Wegener

Phone +49 331 568-1209
Fax +49 331 568-3000
michael.wegener@iap.fraunhofer.de

Dr. Hartmut Krüger

Phone +49 331 568-1920 Fax +49 331 568-3000 hartmut.krueger@iap.fraunhofer.de

www.iap.fraunhofer.com

As electroactive materials, so-called dielectric elastomer actuators (DEA) are developed.

The electrically-controllable large-strain actuation of DEAs is used in artificial

and actuators.

actuation of DEAs is used in artificial muscles and in miniaturized actuators for optical systems. Beside the activities in the field of electromechanical materials,

Fraunhofer IAP also performs material research and transducer development for other sensor purposes such as capacitive, humidity, and magnetic-field sensors.

Basic aspects of the research are material development and composition optimization, evaluation of underlying structure-property relations and process-technique development for transducer materials and contact layers. Here, new techniques such as ink jet printing, air brush and slot-die coating are adapted and used in addition to classical spin coating and solvent casting.